

BC58 with Interbus Interface

Electrical Specifications	
Supply voltage	11- 30 V DC
Max. current consumption ST / MT	220mA / 250 mA
Interface	Interbus, ENCOM Profil K 3 (programable), K 2
DÜ format	Sypi Adresse 0123, Byte Nr. 3210
Programmable funktions	Direction, Skalierungsfaktor, Preset, Offset
Output Code	32 Bit Binär
Baud rate	500 Kbaud ENCOM
Resolution Singleturn	10 – 17 Bit , 12 Bit MT Variante
Resolution Mutltiurn	12 Bit
ID.Code K 3	37H (055 dezimal)
Connection	Enclosure with 2 x connector, Encolure with 3 x PG
Mechanical Specifications	
Permissible temp. range	- 40 ° C bis + 85 ° C
Weight ca, ST/ MT	350 g / 400 g

Order No:

BC 58 / 1212 E K.42 I3 I

Resolution	Supply voltage	Flange	Protection	Shaft	Interface	Connection
0010 10 Bit ST	E = 10-30 V	S.41 Sychro	IP 64	6 mm	I2 Interbus K2	I = 2 x 12 pins Connector
0012 12 Bit ST		S.71 Sychro	IP 67	6 mm	I3 Interbus K 3	Z = 3 x PG
0013 13 Bit ST		K.42 Clamp	IP 64	10 mm		Bus Terminal
0014 14 Bit ST		K.72 Clamp	IP 67	10 mm		
1212 12 MT+ 12 S		F.42 Plug-shaft	IP 64	10 mm H-shaft		
		F.47 Plug-shaft	IP 64	12 mm H-shaft		